

ES4324

L2 Gigabit Lite Switch



Product Overview

The Edge-Core ES4324 is Gigabit Ethernet Layer 2/4 switch featuring 24 RJ-45 10/100/1000 ports and 4 combo Gigabit Ethernet RJ-45/SFP ports. This switch enables networks of all sizes to introduce Gigabit Ethernet with management features targeted to meet the needs of the SMB network, and Gigabit to the desktop for power users. It is packed with features and is a cost-effective solution that brings continuous availability, QoS priority queuing with classification and prioritization at Layer2/Layer4.

Ethernet Switch

Key Features and Benefits

Performance and Scalability

With 48Gbps switching capacity, the ES4324 delivers wire-speed and Non-Blocking switching performance on all gigabit ports, allowing users to take full advantage of existing high-performance, gigabit integrated Servers, PCs and laptops by significantly improving the responsiveness of applications and file transfer times.

There are four Gigabit Ethernet combo ports for uplink flexibility, allowing copper or fiber uplinks.

Continuous Availability

IEEE 802.1w Rapid Spanning Tree Protocol provides a loop-free network and redundant links to the core network with rapid convergence, to ensure faster recovery from failed links, enhancing overall network stability and reliability.

IEEE 802.3ad Link Aggregation Control Protocol (LACP) increases bandwidth by automatically aggregating several physical links together as a logical trunk and providing load balancing and fault tolerance for uplink connections.

IGMP snooping prevents flooding of IP multicast traffic and limits bandwidth intensive video traffic to only the subscribers.

Broadcast Storm Control prevents faulty end stations from degrading overall system performance.

IEEE 802.1Q-in-Q VLAN Tag is purpose to expand the VLAN space by tagging the tagged packets, thus producing a "double-tagged" frame. The expanded VLAN space allows the service provider to provide certain services, such as Internet access on specific VLANs for specific customers, and yet still allows the service provider to provide other types of services for their other customers on other VLANs.

Comprehensive QoS

4 egress queues per port enable differentiated management of up to 4 traffic types.

Traffic is prioritized according to 802.1p, DSCP, giving optimal performance to real-time applications such as voice and video.

Asymmetric bidirectional rate-limiting, per port or per traffic class, preserves network bandwidth and allowing maximum control of network resources.

Enhanced Security

Port Security ensures access to switch ports based on MAC address, limits the total number of devices from using a switch port and protects against MAC flooding attacks.

IEEE 802.1X port-based access control ensures all users are authorized before being granted access to the network. User authentication is carried out using any standard-based RADIUS server.

Simple Management

Industry standard Command Line Interface (CLI) via console port or Telnet provides a common user interface and command set for users to manipulate the switch.

Embedded user friendly web interface helps users quickly and simply configure switches.

ES4324 Product Specifications

Features

Physical Ports

24 RJ-45 10/100/1000Base-T ports with MDI-II/MDI-X
4 Combo G (RJ-45/SFP) ports
1 RS-232 DB-9 console port

Performance

Switching Capability: 48Gbps
Forwarding Rate: 35.7Mpps
MAC Address Table Size: 8K
Packet Buffer Size: 0.4Mb

L2 Features

Auto-negotiation for port speed and duplex mode
Flow Control:

- IEEE 802.3x for full duplex mode
- Store & Forward switching methods
- Back-Pressure for half duplex mode

Spanning Tree Protocol:

- IEEE 802.1D Spanning Tree Protocol (STP)
- IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)

VLANs:

- Supports 255 IEEE 802.1Q VLANs
- Port-based VLANs

Link Aggregation:

- Static Trunk
- IEEE 802.3ad Link Aggregation Control Protocol
- Trunk groups: 8, Trunk links: 2~8

IGMP Snooping:

- IGMP v1, v2 and v3 snooping
- IGMP Queried

Supports QinQ
Supports jumbo frames up to 9KB

QoS Features

Priority Queues: 4 hardware queues per port
Traffic classification based on IEEE 802.1p CoS, DSCP
Supports WRR and Strict scheduling
Bandwidth Control:

- Egress rate limiting: 128Kbps/1Mbps/10Mbps/30Mbps/100Mbps granularity
- Ingress rate limiting: 128Kbps/1Mbps/10Mbps/30Mbps/100Mbps granularity

Security

Supports IEEE 802.1X port-based access control
Access Control List
IP Filter

Management

Switch Management:

- CLI via console port
- WEB management
- SNMP v1, v2c,

Firmware & Configuration:

- Firmware upgrade via WEB

Supports RMON (groups 1)
(Optional) ECview is a powerful network management system that maximizes the capabilities of Edge-Core devices with:

- Topology Management
- Performance Management
- Configuration Management
- Event Management
- SNMP Management

Mechanical

Dimensions (H x W x D): 4.0 x 44.5 x 17cm(1RU)
19" rack-mount metal case
LED Indicators: Port, Link/Activity, 1000Mbps

Safety

CSA/NRTL (UL60950, CSA 22.2. NO60950-1)
TUV/GS (EN60950-1)
CB(IEC60950-1)

Electromagnetic Compatibility

CE Mark
FCC Class A
VCCI Class A

Environmental Specifications

Temperature:

- IEC 68-2-14
- 0°C to 45°C (Standard Operating)
- -40°C to 70°C (Non-Operating)

Humidity: 10% to 90% (Non-condensing)
Vibration: IEC 68-2-36, IEC 68-2-6
Shock: IEC 68-2-29
Drop: IEC 68-2-32

Warranty

Limited lifetime warranty

Ordering Information

Optional Accessories

ET4201-SX
ET4201-LX
ET4201-LHX
ET4201-ZX

ECview

Product Description

Small Form Factor Pluggable (Distance: 500m; Wavelength: 850nm)
Small Form Factor Pluggable (Distance: 10km; Wavelength: 1310nm)
Small Form Factor Pluggable (Distance: 40km; Wavelength: 1310nm)
Small Form Factor Pluggable (Distance: 80km; Wavelength: 1550nm)

SNMP Network Management Software



Powered by Accton

TEL: 886-3-5053801 FAX: 886-3-5780764
No.1, Creation Rd. III, Science-based Industrial Park Hsinchu Taiwan 30077
sales_ec@edge-core.com
www.edge-core.com

DS_ES4324
2006.08