

AS6712-32X 40GbE Data Center Switch Bare-Metal Hardware

Switch Design Accepted by Open Compute Project



Product Overview

The Edgecore AS6712-32X is a Top-Rack or spine switch for high-performance data centers. In a compact 1RU form factor, the switch provides line-rate L2 and L3 switching across 32 x QSFP+ ports, supporting 32 x 40 GbE connections or 96 x 10 GbE + 8 x 40 G connections. The AS6712-32X can be deployed as a TOR switch supporting 10 GbE or 40 GbE server connections, or as a spine switch supporting 10 GbE or 40 GbE spine interconnects. The AS6712-32X is a bare-metal switch loaded with the Open Network Install Environment (ONIE), which supports the installation of compatible open source and commercial Network Operating Systems for different network use cases and requirements.

Key Features and Benefits

- Cost-effective, bare-metal switch infrastructure for data center fabric.
- 32 fixed x 40 GbE QSFP+ switch ports in compact 1RU form factor, each supporting 40 GbE or 4 x 10 GbE via breakout cables. Maximum 24 x 40GbE QSFP+ switch ports support breakout cables.
- Layer 2 or Layer 3 forwarding of 2.56 Tbps full duplex.
- Supports hot/cold aisle with port-to-power and power-to-port airflow SKUs.
- All ports on front. PSUs and fans inserted from rear.
- Hot swappable, load-sharing redundant AC PSUs.
- 4+1 redundant, hot-swappable fans modules.
- Energy Efficiency: 227 W typical power consumption under line rate traffic using 24 x passive QSFP DAC, 8 x 40GBASE-SR4.
- Hardware switch pre-loaded with Open Network Install Environment (ONIE) for automated loading of compatible open source and commercial NOS offerings.
- Compatible with Open Network Linux (ONL), an open-source, OCP reference NOS.
- Compatible with Cumulus® Linux® r2.5.3 and later version from Cumulus Networks®.
- Compatible with PicOS™ r2.6.4 and later version from Pica8 Inc.
- Compatible with Switch Light OS from Big Switch Networks and their Big Monitoring Fabric™ and Big Cloud Fabric™ SDN applications.
- Compatible with SnapRoute FlexSwitch software.
- Compatible with Pluribus Netvisor® OS (ONVL) version 2.5 and later from Pluribus Networks.

Data Center Switch

Features

Ports

Switch Ports:
32 QSFP+ fixed ports: 40 GbE or 4 x 10 GbE per port
Total switch capacity: 32 x 40 GbE
Management ports on port side:
1 x RJ-45 serial console
1 x RJ-45 100/1000BASE-T management port
1 x USB Type A storage port

Key Components

Switch Silicon: Broadcom BCM56850 Trident II 1.28 Tbps
Intel Atom C2538 quad-core 2.4 GHz x86 processor
8 GB SO-DIMM DDR3 RAM with ECC
16 MB SPI flash
8 GB NAND flash
mSATA SSD (Optional)

Performance

Switching Capacity: 2.56 Tbps full duplex
Forwarding Rate: 1.44 Bpps
Jumbo frames support up to 9216 Bytes
Packet Buffer Size: 12 MB integrated packet buffer
Latency (RFC2544): 600 to 720 ns cut-through mode
Subject to NOS:
MAC Addresses: 32 K min./288 K max.
VLAN IDs: 4 K
IPv4: 16 K min./112 K max. host entries; 16K LPM entries with TCAM-only mode
IPv6: 8 K min./56 K max. host entries; IPv6/64=8 K TCAM-only mode

Supported Optics and Cables

QSFP+ Ports:
40GBASE-CR4 DAC; 0.5 m to 5 m; passive and active
40GBASE-CR4 DAC to 4 x SFP+ 10GBASE-CR DAC; 0.5 to 5 m
40GBASE-SR4: Up to 100 m over OM3 MMF, 150 m over OM4 MMF
40GBASE-SR4 to 4 x 10GBASE-SR: 100 m over OM3, 150 m OM4
40GBASE-LR4: Up to 10 km over SMF

Physical and Environmental

Dimensions (WxDxH): 43.84 x 51.5 x 4.35 cm (17.26 x 20.28 x 1.71 in)
Weight: 9.65 kg (21.27 lb), with two installed PSUs
Fans: 4+1 redundant, hot-swappable
Operating Temperature: 0°C to 40°C (32°F to 104°F)
Storage Temperature: -40°C to 70°C (-40°F to 158°F)
Operating Humidity: 5% to 95% non-condensing

Software

Switch is loaded with Open Network Install Environment (ONIE) software installer
Compatible with the following NOS options:
Cumulus® Linux® r2.5.3 and later version from Cumulus Networks®
Open Network Linux, the open-source, OCP reference NOS
PicOS™ r2.6.4 and later version from Pica8 Inc.
Switch Light OS from Big Switch Networks, and their Big Monitoring Fabric and Big Cloud Fabric applications
FlexSwitch software from SnapRoute
Pluribus Networks – Netvisor® OS (ONVL)

LEDs

40G QSFP+ Port LEDs: Link Status, Activity
Ethernet Management Port LED: Link Status, Activity
Console Port LED: Link Status
System LEDs: Diagnostic, Locator

Power

PSUs: 2 redundant, load-sharing, hot-swappable AC or -48 VDC
Input Voltage: 90 to 264 VAC at 50-60 Hz. -48 to -72 VDC.
Input Current: 10 A@100/120 VAC, 5 A@200/240 VAC
PSU Efficiency: Up to 93% for AC PSUs
Power input option: 12 VDC
Max Power: 370 W, 32 x 40GBASE-LR4, line rate traffic
Typical Power: 261 W, 32 x 40GBASE-SR4, line rate traffic
Typical Power (TOR): 227 W, 24 x passive QSFP DAC, 8 x 40GBASE-SR4, line rate traffic

Regulatory

EMI
CE Mark (EN55022 Class A)
FCC Part 15 Class A
VCCI
Safety
CB, EN 60950
UL/CUL
Environmental:
Temperature: IEC 68-2-14
Drop test: ISTA 2A
RoHS-6 Compliant
Vibration: IEC 68-2-36, IEC 68-2-6
Shock: IEC 68-2-29
Country of Origin: Taiwan (TAA Compliant)

Warranty

Please check www.edge-core.com for the warranty terms in your country.

For More Information

To find out more about Edgecore Networks Corporation products and solutions, visit www.edge-core.com.

About Edgecore Networks Corporation

Edgecore Networks Corporation is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edgecore Networks Corporation delivers the software and systems that transform the way the world connects. Edgecore Networks Corporation serves customers and partners worldwide. Additional information can be found at www.edge-core.com.

Edgecore Networks Corporation is a subsidiary of Accton Technology Corporation, the leading network ODM company. The Edgecore data center switches are developed and manufactured by Accton.

To purchase Edgecore Networks solutions, please contact your Edgecore Networks Corporation representatives at +886 3 563 8888 (HQ) or +1 (949)-336-6801 or authorized resellers.

© Copyright 2019 Edgecore Networks Corporation. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edgecore Networks Corporation. Edgecore Networks Corporation shall not be liable for technical or editorial errors or omissions contained herein.

Ordering Information

Base Model: AS6712-32X 32-Port 40G QSFP+; ONIE software installer

Model Number	CPU Module	PSU	Airflow	Region (power cord)
6712-32X-O-AC-F-US	Intel Atom C2538 processor	dual AC PSUs	port-to-power airflow	N. America
6712-32X-O-AC-B-US	Intel Atom C2538 processor	dual AC PSUs	power-to-port airflow	N. America
6712-32X-O-AC-F-EU	Intel Atom C2538 processor	dual AC PSUs	port-to-power airflow	Europe
6712-32X-O-AC-B-EU	Intel Atom C2538 processor	dual AC PSUs	power-to-port airflow	Europe
6712-32X-O-AC-F-UK	Intel Atom C2538 processor	dual AC PSUs	port-to-power airflow	UK
6712-32X-O-AC-B-UK	Intel Atom C2538 processor	dual AC PSUs	power-to-port airflow	UK
6712-32X-O-AC-F-JP	Intel Atom C2538 processor	dual AC PSUs	port-to-power airflow	Japan
6712-32X-O-AC-B-JP	Intel Atom C2538 processor	dual AC PSUs	power-to-port airflow	Japan
6712-32X-O-48V-F	Intel Atom C2538 processor	dual -48V DC PSUs	port-to-power airflow	
6712-32X-O-48V-B	Intel Atom C2538 processor	dual -48V DC PSUs	power-to-port airflow	
PSU-AC-400-F		400W AC Power Supply FRU	port-to-power airflow	no power cord
PSU-AC-400-B		400W AC Power Supply FRU	power-to-port airflow	no power cord
PSU-48V-400-F		-48V DC Power Supply FRU	port-to-power airflow	no power cord
PSU-48V-400-B		-48V DC Power Supply FRU	power-to-port airflow	no power cord
FAN-1U-1x1D-F		Fan Module FRU	port-to-power airflow	
FAN-1U-1x1D-B		Fan Module FRU	power-to-port airflow	
Model Number	Description			
67xx-32X-SVC-RTF	AS67xx-32X series, Annual Hardware Service, Return-to-Factory, after warranty. 3 year warranty included already with the product, maximum 2 additional years per product.			
RKIT-85-6712	AS6712-32X rear rack mount bracket, front rack mount bracket and screws for mounting into 19 inch standard rack.			
ORSA-1U	Open Rack Switch Adapter, for mounting standard 19 inch form factor 1U switches into 21 inch Open Rack			
CBL-PWR-US	AC Power Cable - US (125V/13A, 1830mm) – only required with spare power supplies			
CBL-PWR-EU	AC Power Cable - Europe (250V/10A, 1830mm) – only required with spare power supplies			
CBL-PWR-UK	AC Power Cable - UK (250V/10A, 1830mm) – only required with spare power supplies			
CBL-PWR-JP	AC Power Cable - Japan – only required with spare power supplies			