

25G 100m SFP28 Transceiver

ET7302-SR



Product Features

- Up to 25.78 Gb/s bi-directional data links
- Electrical interface specifications per SFF-8431
- Management interface specifications per SFF-8432 and SFF-8472
- Build-in dual CDR with shut-off control
- SFP28 MSA package with duplex LC connector
- Uncooled 850 nm VCSEL Laser
- Up to 70 m on OM3 MMF and 100 m on OM4 MMF
- Single +3.3 V power supply
- Class 1 laser safety certified
- 1.0W maximum power consumption with established link
- Operating Temperature: 0°C to +70°C
- RoHS Compliant

Applications

- High-speed storage area networks
- 25G high-speed interconnection


Description

The ET7302-SR SFP28 transceiver is compliant with the 25 Gigabit Small Form Factor Pluggable SFP28 Multi-Source Agreement (MSA) SFF-8431 Rev. 4.1 and SFF-8472 Rev. 12.0, and is designed for use at up to a 25.78 Gb/s data rate and a 100 m link length. It is compatible with SFF-8432.

Ordering Information

Part Number	Transmitter	Output Power	Sensitivity	Reach	Temp	DDM	RoHS
ET7302-SR	850nm	-8.4 ~ +2.4 dBm	<-10.3 dBm	OM4: 100 m OM3: 70 m	0~ 70°C	Available	Compliant

Pin Description



Absolute Maximum Ratings

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. These are absolute stress ratings only. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of the datasheet. Exposure to absolute maximum ratings for extended periods can adversely affect device reliability.

Parameter	Symbol	Minimum	Maximum	Unit
Storage Temperature	Ts	-40	85	°C
Relative Humidity	RH	5	95	%
Supply Voltage	Vcc	-0.5	4.0	V

Recommended Operating Conditions

Parameter	Symbol	Minimum	Typical	Maximum	Unit	
Operating Case Temperature	T _c	0	25	70	°C	
Supply Voltage	V _{cc}	3.135	3.3	3.465	V	
Data Rate Per Channel	-	-	25.78	-	Gb/s	

Transceiver Electrical Characteristics

Parameter	Symbol	Minimum	Typical	Maximum	Unit	Notes
Module Supply Current	I _{cc}	-	-	290	mA	
Power Dissipation	P _b	-	-	1.5 W	W	

Transmitter Optical Characteristics

Parameter	Symbol	Minimum	Typical	Maximum	Unit	Notes
Launch Optical Power	P _o	-8.4	-	+2.4	dBm	
Extinction Ratio	ER	2	-	-	dB	
Center Wavelength Range	λ _c	840	850	860	nm	

Receiver Optical Characteristics

Parameter	Symbol	Minimum	Typical	Maximum	Unit	Notes
Center Wavelength	λ _c	840	850	860	nm	
Receiver OMA Sensitivity	RxSENS	-	-	-10.3	dBm	
Receiver Overload (P _{avg})	P _{OL}	2.5	-	-	dBm	

Warranty

Please check www.edge-core.com for the warranty terms in your country.

For More Information

To find out more about Edgecore Networks Corporation products and solutions, visit www.edge-core.com.

About Edgecore Networks Corporation

Edgecore Networks Corporation is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edgecore Networks Corporation delivers the software and systems that transform the way the world connects. Edgecore Networks Corporation serves customers and partners worldwide. Additional information can be found at www.edge-core.com.

Edgecore Networks Corporation is a subsidiary of Accton Technology Corporation, the leading network ODM company. The Edgecore data center switches are developed and manufactured by Accton.

To purchase Edgecore Networks solutions, please contact your Edgecore Networks Corporation representatives at +886 3 563 8888 (HQ) or +1 (949)-336-6801 or authorized resellers.

© Copyright 2021 Edgecore Networks Corporation. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edgecore Networks Corporation. Edgecore Networks Corporation shall not be liable for technical or editorial errors or omissions contained herein.